

Partition Cleaning and Care Instructions

BioPrism® Solid Surface

Cleaning and Care of your BioPrism® Solid Surface Partition Panels

There are two types of solid surface finishes: matte and satin. Lighter colors are finished with a matte finish, and darker colors receive a satin finish.

To prevent the build up of a film on the surface, it is very important to wipe the surface completely dry after cleaning.

Note:

- Do not spray water directly onto wood core partitions.

Surfaces - Cleaning all Finishes

Cleaning

Spray entire surface with LYSOL Power & Free Bathroom Cleaner, wipe with a clean cloth or sponge. No rinsing required.

Prevent Hard Water Marks

Rinse and wipe completely dry after cleaning. On vertical surfaces a squeegee works well.

Removing Soap Scum, Limescale and Rust Stains

Spray entire surface with LYSOL Power & Free Bathroom Cleaner, allow product to sit for 10 minutes before wiping with a clean cloth or sponge. Repeat if necessary.

Removing Hard Water Marks

Use Cleaner formulated for removing hard water marks, such as CLR.

Disinfecting

Occasionally wipe surface with diluted household bleach - 1:10 (1.5 cups of bleach to 1 gallon of water, As recommended by the Centers For Disease Control and Prevention for disinfection and sterilization of surfaces)

Preventing Other Damage

In most cases BioPrism® Solid Surface can be repaired if damaged. Be sure to follow these guidelines to help you prevent permanent damage to your solid surface panels:

- Avoid getting strong chemicals, such as paint removers, oven cleaners, etc., on your BioPrism® Solid Surface. If a spill does occur, promptly flush the surface with water to fully rinse off the chemical.

Renewing the Finish

Sanding:

Using a 5" or 6" random-orbital sander, move the sander in an orbital pattern, overlapping each pass by 50%. Sand slowly and evenly, keeping the micron paper clean from sanding dust (Check paper frequently).

Matte Finish (Class A & A1)

- Use a 100 micron sanding pad to remove marks and scratches and even out the finish.
The easily maintained matte finish is suitable for high use areas.

Satin Finish (Class B)

- Remove marks and scratches with a 100 micron sanding pad.
- Repeat the process with a 60 micron sanding pad.
- Use a Scotch-Brite® pad (#7447 Maroon, Very Fine, 320-400 Grit) under the sanding pad to even out the finish.
- Repeat the process with a Scotch-Brite® pad (#7448 Gray, Ultra Fine, 600-800 Grit).

Stainless Steel Hardware Cleaning Guide

Note:

- Do not use cleaners containing Muriatic or Hydrochloric acid, these chemicals may damage or discolor the stainless steel finish.
- Do not use steel wool as it may leave behind steel particles which may cause rust stains.

Removing smudges and fingerprints

Wipe surface with quality stainless steel cleaner/polish. Apply using a soft, non-abrasive cloth. Always follow cleaner/polish directions.

Removing dirt and debris

Wash surface with a mild liquid soap. Apply using a soft, non-abrasive cloth. Rinse thoroughly with clean soft water. Wipe surface with stainless steel cleaner/polish.

Removing rust stains

Wash surface with CLR cleaner. Use recommended solution. Apply using a soft non-abrasive sponge. Rinse thoroughly with clean soft water. Wipe surface with stainless steel cleaner/polish.

Renewing a satin finish

Apply a stainless steel polish/cleaner using a synthetic, abrasive, pad such as a Scotch Brite® pad. Be sure to rub in the direction of the grain.

IPC.3053/REV.2

Installation Hotline • 866.EZINPRO
Inprocorp.com • 800.222.5556 • 262.679.9010
World Headquarters S80 W18766 Apollo Drive, Muskego, WI 53150 USA

ENDURANT® •
WASHROOM SYSTEMS

Partition Cleaning and Care Instructions

BioPrism® Solid Surface

Note:

- After cleaning tough problems, let dry, and expose to air for at least 24 hours to allow “healing” of the stainless steel surface.

Piano Hinge Routine Maintenance

The piano hinge is a metal-on-metal design which requires routine maintenance in order to prevent it from squeaking or binding.

- Clean hinge to remove any dust, dirt, or debris.
- Lubricate hinge with a PTFE (Teflon) based lubricant.

Note:

- Do not use machine oil or liquid WD-40, these lubricants will collect dust and dirt.

Sources for materials mentioned above:

CLR® Registered trademark of Jelmar	Local Retail
Clean EnCounters® Registered trademark of Stone Care International	Stone Care International (800) 839-1654
Scotch Brite™ Registered trademark of 3M Company	Local Retail
Soft Scrub® Registered trademark of the Dial Corporation	Local Retail
Rock Doctor Granite Polish Rock Doctor Products, a division of Apex Products	Local Retail
LYSOL Power & Free Bathroom Cleaner Registered trademark of Reckitt Benckiser, Inc	Local Retail

When used properly, LYSOL Power & Free Bathroom Cleaner kills the following bacteria and viruses on hard non-porous surfaces: Salmonella enteric (Salmonella), Escherichia coli O148:H7, Pseudomonas aeruginosa, Staphylococcus aureus (Staph), Avian Influenza AH1N1, Herpes Symplex Virus Type 1, Rhinovirus Type 37, Rotavirus WA (Source: LYSOL website)

Quality Assurance

With proper care, your BioPrism® Solid Surface can stay looking like new. Your Inpro® BioPrism® Solid Surface Partitions carry a 5-year Limited Warranty.